

# JALNATION ESD

## JVJV203

S3S CI FO SR

EN ISO 20345:2022

35 to 48



# HELIUM<sub>2</sub>

ASSEMBLÉ  
EN  
FRANCE

LINK-ESD



- **Putek® STAR LIGHT upper**
- **PU/PU BASF® sole**
- **ESD / Dissipative**
- **Aluminum safety toe cap type B and midsole no metallic S**

- ❖ Low safety shoe urban sport type **designed with technology combining performance and lightness**, black color.
- ❖ Chaussures électrostatiques dissipatrices **ESD** de classe environnementale II protégeant les dispositifs électroniques contre les phénomènes de décharge électrostatique, testées suivant la **norme EN 61340-4-3/4-5/5-1**.
- ❖ **Putek® STAR** Upper, highly resistant to abrasion, water-repellent and breathable. Anti-abrasion reinforcement on the front. Reflective tape at the heel.
- ❖ Breathable upper lining in **3D mesh**, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the shoes.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Lace up on 4 perforations and one pair of non-metallic eyelets. Flat lace 100 cm.
- ❖ **SOFT LIGHT** hygiene insole in ultra-lightweight expanded polymer, cushions pressure points, improves weight distribution and absorbs heel impact. Anatomically shaped, perforated and equipped with the innovative **Link ESD™** multi-contact static dissipation system.
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ **PREM-Alu B** toe-cap in aluminium resisting an impact of an energy of 200 joules. Minimum height after test  $\geq 4$ mm in relation to the Type A toe cap in accordance with **Standard 22568-1:2019**.
- ❖ Antiperforation inner sole and insert in non-woven textile **FLEX-LIGHT By Jallatte S** type is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with **standard 22568-4:2021**, 54% lighter than a standard insert, antistatic, sewn directly onto the upper and **covering 100% of the foot** for total protection.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Innovative HELIUM sole** in bi-component **PU LIGHT/ PU** from **BASF®**, specially formulated for an incomparably light feel and absolute comfort.



### Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

- A- Heel to the front **0,40** ( $\geq 0,31$ )
- B- Front to back **0,38** ( $\geq 0,36$ )

Additional requirement **SR** : Ceramic /Glycerin

- C- Heel to the front **0,25** ( $\geq 0,19$ )
- D- Front to back **0,23** ( $\geq 0,22$ )

- Polyurethane outsole.
- **Special low-density PU comfort formulation.**
  - Lighter but just as effective as conventional polyurethane.
  - Guarantees a better 'durability/weight' ratio.
  - **Unequaled feeling of lightness.**
  - **Suitable for working environment with few constraints.**
  - Good resistance to oils and hydrocarbons.



# Jallatte®

www.jallatte.com

Weight	Gross weight (42) : 1106 g / Net weight (42) : 900 g			
Size	35 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		335 x 210 x 130	
Cartons (mm)	592 x 212 x 313	592 x 410 x 313	685 x 440 x 356	680 x 234 x 356

Non contractual document  
Copyright JALLATTE  
Limited distribution

15/12/2025