

GOTLAND NEW S1PS FO SR

KU434N

CE EN ISO 20345:2022 S1PS FO SR

LOW SAFETY SHOE

37-39

KUBE Supergrip

Low safety shoe made of 1.8-2.0 mm thick **MICRO-tech** fabric and breathable, abrasion-resistant mesh.

Highly breathable and abrasion-resistant fabric lining. Soft, lined and padded tongue.

CLICK OPEN lacing system.

200J composite polymer-based athermic toe cap in accordance/in compliance with with **EN 22568**.

LAMINA PS composite fabric anti-puncture flexible according to **EN 22568**.

SOLE KUBE two-density polyurethane antistatic, resistant to hydrolysis **ISO 5423:92**

hydrocarbon and abrasion resistant, anti-shock and anti-slip.

5000 trimaterial insole, extra comfort, breathable, removable, anatomical, absorbent, ESD and antibacterial.




FO sole resistance to hydrocarbons

SR slip resistance

Size 37-49 Shoe weight tg 42 gr. 515





** The calculated weight excludes laces and insoles.*

↪ **AREAS OF APPLICATION**







-  **Logistics and Light Industry**
-  **Automotive Components**
-  **Metal and Wood Carpentry**



↪ **CERTIFICATIONS APPLIED**

-  **PS Puncture Resistance with Non-Metallic Insert (nail Ø 3.0mm)**
-  **Heel Energy Absorption**
-  **Hydrocarbon Resistance**
-  **DGUV 112-191**

↪ **TECHNOLOGIES AND MATERIALS**


-  **No metal**
-  **High Breathability**
-  **Mondo Point 11**
-  **Extreme Lightness**
-  **Slip Resistance (optional glycerin test)**
-  **Click Open Lacing System**

↪ **ANTI-SLIP RESULTS**

**after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31 0.56	≥ 0.36 0.45		≥ 0.19 0.35	≥ 0.22 0.35
SRA Ceramic + Nails	Flat	Heel	SRB Steel + Glicerol	Flat	Heel
	≥ 0.32 0.39	≥ 0.28 0.37		≥ 0.18 0.30	≥ 0.13 0.20

↳ PLUS



Click Open Lacing System

The Click Open system allows for rapid shoe donning and removal via a rotating knob. A stainless steel wire around the instep ensures a uniform, stable fit, enhancing comfort and safety. Since there are no laces to come undone, it minimizes trip risks and internal friction—ideal for glove-wearing operators or those who change shoes frequently.

↳ SOLE

KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slipperiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

