

JALTRAILER ESD JIJI184

* International Patent

INDUSTRY_{4.0}



S3S SC CI LG FO SR
EN ISO 20345:2022
35 to 48



Link-ESD



- Water-repellent full-grain leather
- PU/PU sole by BASF®
- ESD / Dissipative
- Polymer toe cap type B and non-metallic anti-perforation S

- Outdoor-style safety shoe incorporating **MAXI-Soft Duo™ anti-fatigue technology** designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3/4-5/5-1**.
- Full-grain water-repellent leather upper with pull-up finish, **excellent waterproof leather, no water crossing after 7h test**. Very good breathability (sweating well above the normative requirements). Abrasion-resistant reinforcement at the heel.
- The polyurethane toe cap, having been **SC-rated**, complies with **EN ISO 20345:2021**, which guarantees the footwear's sturdiness and longevity, as well as its increased resistance to impacts and scuffing.
- Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection. TPU reinforcement on malleoli.
- Lined full grain leather tongue with side bellows to keep out dust and dirt.
- Lace up with four pairs of no metallic eyelets and two pairs of **Quick Lio**. Laces 150 cm.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a soft **BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan** insert that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact, static electricity dissipater.
- Ergonomic shoe with broad toe-cap **Springtane type B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.
- The **FleXtane™ S-type** mounting insole by **Jallatte** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with standard **22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and covers **100% of the foot** for all-round protection.
- BASF® PU/PU** sole with an urban sport design, linear profile and excellent slip resistance.



Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)
A- Heel to the front **0,65** (>0,31)
B- Front to back **0,64** (>0,36)

Additional requirement SR : Ceramic /Glycerin
C - Heel to the front **0,31** (>0,19)
D- Front to back **0,38** (>0,22)



- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

Weight	Gross weight (42) : 1666 g / Net weight (42) : 1450 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356

