

JALTEX
00JJV53

Softane
Adventure

Jallatte® GORE-TEX®

S7S SC CI LG FO SR
EN ISO 20345:2022
38 to 47



- **Water-repellent full-grain leather and anti-abrasion**
- **Dual density Softane™ sole**
- **Polymère toe cap type B and no metallic midsole S**
- **Antistatic and amagnétic**

- ❖ High-laced boot style outdoor. Brown and black color.
- ❖ Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. **Excellent impermeability**, no water crossing after 7h test. Very good breathability (evacuation of sweating well above normative requirements).
- ❖ The polyurethane toe cap, having been **SC**-rated, complies with EN ISO 20345:2021, which guarantees the footwear's sturdiness and longevity, as well as its increased resistance to impacts and scuffing.
- ❖ **GORE-TEX®** Performance Comfort Footwear membrane.
- ❖ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Padded, "3D" lined leather tongue to protect the top of the foot, with side bellows to keep out dust and dirt.
- ❖ Fastened by 5 pairs of no metallics lace stays. Laces 120 cm 38 to 41 and 130 cm 42 to 47.
- ❖ Tabs at the back for easy pull-on.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable.
- ❖ Ergonomic shoe with broad toe-cap **SPRINGTANE type B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test ≥ 4 mm in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.
- ❖ **The FlexTane™ S-type** mounting insole by Jallatte is puncture-resistant to sharp objects up to 3mm in diameter (Small) in compliance with standard **22568-4:2021**, antistatic, 100% composite, sewn directly onto the upper and covers 100% of the foot for all-round protection.
- ❖ Heel stiffener to reinforce the heel seat
- ❖ Dual density **Softane™ PU** sole, **robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated. Pu reinforcement to the front of the sole. Sole features with the JAL'GRIP SYSTEM, a LADDER GRIP double-release unhooking system as standard, is fully **LG**-rated in compliance with standard EN ISO 20345:2021, which enables ladder attachment and prevents the risk of falls from heights.

Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)
A- Heel to the front **0,36** ($\geq 0,31$)
B- Front to back **0,42** ($\geq 0,36$)

Additional requirement SR : Ceramic /Glycerin
C - Heel to the front **0,23** ($\geq 0,19$)
D- Front to back **0,33** ($\geq 0,22$)

- Softane™ comfort layer, density 0.45 / Outsole density = 1.10.
- High abrasion resistance .
- Highly resistant to oils and hydrocarbons.
- Heel shock absorption > 20 Joules.
- Rugged sole pattern with self-cleaning treads, depth 6,5 mm.
- Very flat sole with a large contact area with the ground. Improved stability.

Weight	Gross weight (42) : 1682 g / Net weight (42) : 1464 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356



www.jallatte.com