

JALASKA 00J0266

Softane™
Tradition

S3 FO SR
EN ISO 20345:2022
36 to 48



- Full grain **AP 23** leather
- **Softane™** dual-density sole
- Steel toe cap / Steel midsole
- Antistatic

- ❖ Natural-coloured boot with 2 leather side tabs for rapid pull-on. Stem height: 23.4 cm.
- ❖ Boot in full grain leather **AP 23**, water and oil resistant : a Jallatte exclusive
 - **10 to 15% thicker** (2.4mm) than most leathers usually used in safety shoe manufacture.
 - **Upper resistance to water penetration:** to European standard level or more.
- ❖ Flat binding at top of quarters.
- ❖ Full-size inlay, removable, anti-bacterial treated, anatomical and comprising heel shock absorber. High capacity to absorb and desorb perspiration.
- ❖ Forefoot lining, resistant to abrasion and perspiration acids.
- ❖ Perforated steel toe-cap (patented) – 200 J.
- ❖ Puncture-resistant stainless steel midsole .
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Dual density **Softane™** sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability

**Slip resistance tests results EN Standard ISO
20345:2022**

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,36** (≥ 0,31)

B- Front to back **0,65** (≥ 0,36)

Additional requirement SR : Ceramic /Glycerin

C - Heel to the front **0,23** (≥ 0,19)

D- Front to back **0,25** (≥ 0,22)

- ✓ Wraps round the foot for increased stability when walking.
- ✓ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm³
- ✓ Heel schock absorption 29 Joules.



Weight	Gross weight (42) : 1740 g / Net weight (42) : 1420 g	
Size	35 à 45	46 au 48
Packaging	5 pairs	
Box shoes (mm)	337 x 328 x 135	365 x 320 x 134
Cartons (mm)	625 x 425 x 343	690 x 330 x 383

Jallatte®

www.jallatte.com